

- High quality **CertiMet** digital indicator with IP65 proof
- PRESET, mm/inch, HOLD function
- USB data transfer
- CR2032 3V battery
- Calibration certificate included (ISO17025 (Ilac MRA))


**VIDEO**

**RANGE UP TO 200MM**

**PRESET  
FUNCTION**

| Item No   | Range  |        | Resolution |          | Accuracy | Force   | Proof | mm/inch | Preset | ABS | USB DATA |
|-----------|--------|--------|------------|----------|----------|---------|-------|---------|--------|-----|----------|
|           | mm     | inch   | mm         | inch     | μm       | N       |       |         |        |     |          |
| 120125131 |        |        | 0,01       | 0.0005"  | ±10      |         | IP65  | •       | •      | •   | •        |
| 120125132 |        |        |            |          | ±6       |         |       | •       | •      | •   | •        |
| 120125133 | 0-12,7 | 0-0,5" | 0,001      | 0.00005" | ±4       | 0.6-1   |       | •       | •      | •   | •        |
| 120125134 |        |        |            |          | ±3       |         |       | •       | •      | •   | •        |
| 120125135 |        |        |            |          | ±2       |         |       | •       | •      | •   | •        |
| 120125251 |        |        | 0,01       | 0.0005"  | ±10      |         |       | •       | •      | •   | •        |
| 120125252 | 0-25,4 | 0-1"   | 0,001      | 0.00005" | ±6       | 0.7-1.2 |       | •       | •      | •   | •        |
| 120125253 |        |        |            |          | ±4       |         |       | •       | •      | •   | •        |
| 120125500 |        |        | 0,01       | 0.0005"  | ±20      |         |       | •       | •      | •   | •        |
| 120125502 | 0-50,8 | 0-2"   | 0,001      | 0.00005" | ±7       | 1.2-2.2 |       | •       | •      | •   | •        |
| 120125503 |        |        |            |          | ±5       |         |       | •       | •      | •   | •        |
| 120125901 |        |        | 0,01       | 0.0005"  | ±20      |         |       | •       | •      | •   | •        |
| 120125902 | 0-100  | 0-4"   | 0,001      | 0.00005" | ±12      |         |       | •       | •      | •   | •        |
| 120125904 |        |        |            |          | ±8       |         |       | •       | •      | •   | •        |
| 120125951 |        |        | 0,01       | 0.0005"  | ±30      |         |       | •       | •      | •   | •        |
| 120125952 | 0-150  | 0-6"   | 0,001      | 0.00005" | ±20      | 3-5     |       | •       | •      | •   | •        |
| 120125954 |        |        |            |          | ±10      |         |       | •       | •      | •   | •        |
| 120125961 |        |        | 0,01       | 0.0005"  | ±30      |         |       | •       | •      | •   | •        |
| 120125962 | 0-200  | 0-8"   | 0,001      | 0.00005" | ±20      |         |       | •       | •      | •   | •        |
| 120125964 |        |        |            |          | ±10      |         |       | •       | •      | •   | •        |

## DELIVERY SET


**CALIBRATION PROTOCOL**

## OPTIONAL

**141083000** USB HID DATA  
TRANSFER CABLE 2.5M  
DIRECT DATA TRANSFER, LIKE A  
KEYBOARD


**STANDS**
