

TABLET EXTRA LONG JAW CALIPER

- Industry 4.0 adopted Extra long jaw Tablet caliper with computerized MICS system with 2.4" color Touchscreen
- Patents US10184772, UA111194, UA112361, UA121681, UA2022205040
- Functions: On-line Graphic, Analog scale, Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction
- Measuring HUB: Wireless MICROTECH instrument connection, Synchronization, 2D mode, 2D Graph, Probe mode, Compensation
- Aluminium construction with precision linear guides
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- 4 MODES DATA TRANSFER: WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))




WIRELESS TO MDS APP
 WIRELESS HID+MAC
 USB HID

Windows Android LINUX macOS iOS

ROLL SLIDING SYSTEM

- Light aluminium base
- 2x steel roll for easy sliding



ON-LINE GRAPHIC MODE

CUSTOM RANGE AND JAWS FOR REQUEST

Item No	Range		Resol.	Jaws	Accu- racy	Weight	Measuring HUB	Analog scale	Graphic	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB HID	FW update	Display			
	mm	inch																						mm	mm	µm
142408442	0-800	0-32"	0,01	400	±30	3,9	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
142411442	0-1000	0-40'		400	±40	4,3	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
142411462				600	±60	4,7	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
142418442	0-1800	0-60"		400	±60	6,2	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
142418462				600	±80	6,6	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
142120142	0-2000	0-80"		400	±60	17,5	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
142120162				600	±85	18,0	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
142120102	0-2500	0-100"		1000	±120	19,0	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
142125142				400	±90	20,0	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
142125162	0-3000	0-120"		600	±105	20,5	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
142125102				1000	±140	21,5	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
142130142	0-3500	0-140"		400	±100	24,0	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
142130162				600	±110	24,5	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
142130102	0-3500	0-140"		1000	±160	25,5	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
142135142				400	±120	26,5	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
142135162	0-3500	0-140"		600	±160	27,0	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
142135102				1000	±240	28,0	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

DOWNLOAD APP

