

- Bore gauge for measuring minimum distance form the bottom
- Digital MICRON indicator with PRESET, HOLD functions and optional USB data transfer
- **Calibration** certificate included (ISO17025 (Ilac MRA))



Item No	Range	Reso- lution	Accu- racy	Repea- tability	Depth	Base width	Distance from bottom	Tip travel	Weight	Preset	Hold
	mm	mm	μm	μm							
132065032	15-35	0,001	±4	±1	90	11,5	1,5	1,4	0,08	•	•
132065062	25-60		±4		130	18	2	1,6	0,1	•	•
132065152	50-150		±4		150	38	1,5	2,5	0,2	•	•
132065302	100-300		±5		230	66	1,5	3,3	0,4	•	•

COMPLECTATION



OPTIONAL

141083000 USB HID DATA
TRANSFER CABLE 2.5M
DIRECT DATA TRANSFER, LIKE A
KEYBOARD



- Bore gauge for measuring minimum distance from the bottom
- Multifunctional computerized **MICS** indication system with 0.1 micron resolution.
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Iac MRA))



0,1 μm

Item No	Range	Resolution	COMPUTERIZED																				
			Accur.	Repeatability	Depth	Base width	Distance from bottom	Tip travel	Weight	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB	
			μm	μm	mm	mm	mm	mm	mm	kg													
132065038	15-35	0,0001	±3	±1	90	11,5	1,5	1,4	0,25	•	•	•	•	•	•	•	•	•	•	•	•	•	
132065068	25-60		±3		130	18	2	1,6	0,4	•	•	•	•	•	•	•	•	•	•	•	•	•	
132065158	50-150		±3		150	38	1,5	2,5	0,55	•	•	•	•	•	•	•	•	•	•	•	•	•	•
132065308	100-300		±3		230	66	1,5	3,3	0,77	•	•	•	•	•	•	•	•	•	•	•	•	•	•

COMPLECTATION

FREE VERSIONS OF MDS APP

USB DATA/CHARGING CABLE

CALIBRATION PROTOCOL

MADE IN UKRAINE

OPTIONAL

iOT DATA BUTTON

MDS SOFTWARE

STANDARD MDS app

iOT DISPLAY UNIT