



PRESET  
FUNCTION

1 μm

CUSTOM RANGE AND DEPTH FOR REQUEST



HAND LAPPED DISKS  
DIAMETERS 20, 30, 50MM

- CertiMet digital MICRON DISK thickness gauge with range up to 300mm and depth up to 800mm
- Micron Digital indicator IP65 proof with PRESET and HOLD function
- Modifications with DISK D 20, 30, 50mm (Custom Diameters for request)
- Calibration certificate included (ISO17025 (Ilac MRA))

Item No	Range	Reso- lution	Accu- racy	Depth	Contact points D	Lifting device	Force	Weight	Proof	mm/inch	Preset	ABS	USB DATA
	mm	mm	µm	mm	mm		N	kg					
<b>THICKNESS GAUGE with DISK ANVILS 20mm</b>													
137010128D2	0-10	0,001	±12	120	Disk D=20mm	•	0,7-1,3	0,34	IP65	•	•	•	•
137025208D2	0-25		±18	200		•	1,2-1,8	0,66	IP65	•	•	•	•
137025408D2			±25	400		•		1,5	IP65	•	•	•	•
137050308D2	0-50		±25	300		•	1,8-2,3	1,5	IP65	•	•	•	•
137050408D2			±30	400		•		3,3	IP65	•	•	•	•
137050808D2			±40	800		•		4,8	IP65	•	•	•	•
137100408D2	0-100		±30	400		•	2,5-3,3	3,8	IP65	•	•	•	•
137100808D2			±55	800		•		5,4	IP65	•	•	•	•
137150408D2	0-150		±55	400		•	2,9-4,1	8,5	IP65	•	•	•	•
137150808D2			±80	800		•		10,8	IP65	•	•	•	•
137300408D2	150-300		±70	400		•		11,2	IP65	•	•	•	•
137300808D2			±95	800		•		14,6	IP65	•	•	•	•
<b>THICKNESS GAUGE with DISK ANVILS 30mm</b>													
137025208D3	0-25	0,001	±18	200	Disk D=30mm	•	1,2-1,8	0,66	IP65	•	•	•	•
137025408D3			±25	400		•		1,5	IP65	•	•	•	•
137050308D3	0-50		±25	300		•	1,8-2,3	1,5	IP65	•	•	•	•
137050408D3			±30	400		•		3,3	IP65	•	•	•	•
137050808D3			±40	800		•		4,8	IP65	•	•	•	•
137100408D3	0-100		±30	400		•	2,5-3,3	3,8	IP65	•	•	•	•
137100808D3			±55	800		•		5,4	IP65	•	•	•	•
137150408D3	0-150		±55	400		•	2,9-4,1	8,5	IP65	•	•	•	•
137150808D3			±80	800		•		10,8	IP65	•	•	•	•
137300408D3	150-300		±70	400		•		11,2	IP65	•	•	•	•
137300808D3			±95	800		•		14,6	IP65	•	•	•	•
<b>THICKNESS GAUGE with DISK ANVILS 50mm</b>													
137025208D5	0-25	0,001	±18	200	Disk D=50mm	•	1,2-1,8	0,66	IP65	•	•	•	•
137025408D5			±25	400		•		1,5	IP65	•	•	•	•
137050308D5	0-50		±25	300		•	1,8-2,3	1,5	IP65	•	•	•	•
137050408D5			±30	400		•		3,3	IP65	•	•	•	•
137050808D5			±40	800		•		4,8	IP65	•	•	•	•
137100408D5	0-100		±30	400		•	2,5-3,3	3,8	IP65	•	•	•	•
137100808D5			±55	800		•		5,4	IP65	•	•	•	•
137150408D5	0-150		±55	400		•	2,9-4,1	8,5	IP65	•	•	•	•
137150808D5			±80	800		•		10,8	IP65	•	•	•	•
137300408D5	150-300		±70	400		•		11,2	IP65	•	•	•	•
137300808D5			±95	800		•		14,6	IP65	•	•	•	•

## DELIVERY SET



## OPTIONAL

141083000 USB HID DATA  
TRANSFER CABLE 2.5M  
DIRECT DATA TRANSFER, LIKE A  
KEYBOARD

