



TABLET MULTIFUNCTIONAL MICS
2.4" TOUCHSCREEN DISPLAY



DATAmet FUNCTIONS

ANALOG SCALE	COLOR GO / NOGO	COLOR MAX / MIN / RANGE	TIMER	TOUCH PROBE SETTINGS	Formula
GRAPHIC MODE 1D/2D	MEMORY 2000 values	FOLDERS mode	MEMORY STATISTICS	TEMPERATURE COMPENSATION	PASSWORD
DISPLAY & ENERGY	RESOLUTION, mm/inch	WIRELESS to MDS app	WIRELESS & USB HID	HUB mode (2D, Probe)	DEVICE INFO, UPDATE

- Radius gauges and Radius gauges SET for **External & Internal** measurings up to **15m**
- Straight indication RADIUS value on display (no re-calculation needed)
- Functions: On-line Graphic, Analog scale, Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction
- Measuring HUB: Wireless MICROTECH instrument connection, Synchronization, 2D mode, 2D Graph, Probe mode, Compensation
- Memory manager: 2000 values, Folders system, Statistics mode,
- **4 MODES DATA TRANSFER**: WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))

DataMet RADIUS GAUGES

Item No	Radius		Type	Resol.	Accu- racy	Base	Indica- tor range	Measuring HUB	Graphic	Analog scale	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Memory	WIRELESS	USB	
	Range																					
	mm	inch																				
1250511017	5-60	0,2-1,2"	internal & external	1	0,4-1	10	13	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
1250511007	40-1000	2-48"				40		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1250511117	250-7500	10-300"				200	50	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1250511127	500-15000	20-600"				300		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•


DataMet RADIUS GAUGES SET

Item No	Radius		Type	Resol.	Accu- racy	Base	Indica- tor range	Measuring HUB	Graphic	Analog scale	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Memory	WIRELESS	USB
	Range																			
	mm	inch																		
1250512007	5-1500	0,2-80"	internal & external	1	0,4-1	10,30,60,100	13	•	•	•	•	•	•	•	•	•	•	•	•	•
1250513007	5-4000	0,2-160"				10,30,60,100,200		•	•	•	•	•	•	•	•	•	•	•	•	•
1250515007	40-7500	2-300"				40, 200	50	•	•	•	•	•	•	•	•	•	•	•	•	
1250516007	40-15000	2-600"				40, 300		•	•	•	•	•	•	•	•	•	•	•	•	
1250517007	5-15000	0,2-600"				10, 40, 300		•	•	•	•	•	•	•	•	•	•	•	•	

MODBUS DataMet RADIUS GAUGES

Item No	Radius		Type	Resol.	Accu- racy	Base	Indica- tor range	Measuring HUB	Graphic	Analog scale	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Memory	WIRELESS	USB	MODBUS RTU	MODBUS ASCII	MODBUS TCP/IP		
	Range																									
	mm	inch																								
1250511017M	5-60	0,2-1,2"	internal & external	1	0,4-1	10	13	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	option	option		
1250511007M	40-1000	2-48"				40		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			•	•
1250511117M	250-7500	10-300"				200	50	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			•	•
1250511127M	500-15000	20-600"				300		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			•	•

DELIVERY SET



OPTIONAL

