

- **Industry 4.0** adopted sub-micron Computerized thickness gauge with range up to 300mm and depth up to 800mm
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- Modifications with DISK D 20, 30, 50mm (Custom Diameters for request)
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- **Calibration** certificate included (ISO17025 (Ilac MRA))

Item No	Range	Reso- lution	Accu- racy	Depth	Contact points D	Preset	Go/NoGo	Max/Min	Formula	Timer	Memory	WIRELESS	USB					
	mm	mm	µm	mm	mm													
THICKNESS GAUGE with DISK ANVILS 20mm																		
137010127D2	0-10	0,0001	±12	120	Disk D=20mm	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update firmware					
137020127D2	0-20		±15	120		•	•	•	•	•								
137025207D2	0-25		±18	200		•	•	•	•	•								
137025407D2			±25	400		•	•	•	•	•								
137050307D2	0-50		±25	300		•	•	•	•	•								
137050407D2			±30	400		•	•	•	•	•								
137050807D2	0-100		±40	800		•	•	•	•	•								
137100407D2			±30	400		•	•	•	•	•								
137100807D2	0-150		±55	800		•	•	•	•	•								
137150407D2			±55	400		•	•	•	•	•								
137150807D2	150-300		±80	800		•	•	•	•	•								
137300407D2			±70	400		•	•	•	•	•								
137300807D2			±95	800		•	•	•	•	•								
THICKNESS GAUGE with DISK ANVILS 30mm																		
137025207D3	0-25	0,0001	±18	200	Disk D=30mm	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update firmware					
137025407D3			±25	400		•	•	•	•	•								
137050307D3	0-50		±25	300		•	•	•	•	•								
137050407D3			±30	400		•	•	•	•	•								
137050807D3	0-100		±40	800		•	•	•	•	•								
137100407D3			±30	400		•	•	•	•	•								
137100807D3	0-150		±55	800		•	•	•	•	•								
137150407D3			±55	400		•	•	•	•	•								
137150807D3	150-300		±80	800		•	•	•	•	•								
137300407D3			±70	400		•	•	•	•	•								
137300807D3			±95	800		•	•	•	•	•								
THICKNESS GAUGE with DISK ANVILS 50mm																		
137025207D5	0-25		0,0001	±18		200	Disk D=50mm	•	•	•				•	•	Folders / 2000 val	Long range / HID	USB HID / Update firmware
137025407D5				±25		400		•	•	•				•	•			
137050307D5	0-50	±25		300	•	•		•	•	•								
137050407D5		±30		400	•	•		•	•	•								
137050807D5	0-100	±40		800	•	•		•	•	•								
137100407D5		±30		400	•	•		•	•	•								
137100807D5	0-150	±55		800	•	•		•	•	•								
137150407D5		±55		400	•	•		•	•	•								
137150807D5	150-300	±80		800	•	•		•	•	•								
137300407D5		±70		400	•	•		•	•	•								
137300807D5		±95		800	•	•		•	•	•								



CUSTOM RANGE AND DEPTH FOR REQUEST

COMPLECTATION

FREE VERSIONS OF MDS APP

USB DATA/CHARGING CABLE

CALIBRATION PROTOCOL

OPTIONAL

IOT DATA BUTTON

MDS SOFTWARE

STANDARD MDS app

IOT DISPLAY UNIT

MICROTECH MODBUS RTU