



CUSTOM RANGE AND DEPTH FOR REQUEST

DATA MET FUNCTIONS

<p>COLOR GO / NOGO</p>	<p>COLOR MAX / MIN / RANGE</p>	<p>TIMER</p>	<p>FORMULA Ax^2+Bx+C</p>
<p>MEMORY 1000 values</p>	<p>MEMORY STATISTICS</p>	<p>TEMPERATURE COMPENSATION</p>	<p>DEVICE INFO, UPDATE</p>
<p>DISPLAY & ENERGY</p>	<p>RESOLUTION, mm/inch</p>	<p>WIRELESS to MDS app</p>	<p>WIRELESS & USB HID</p>

- **DataMet** Two-point bore gauges with range up to 1500mm and depth up to 2 m
- Carbide tipped measuring pins
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **Quick reading system** (50 value/sec)
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- **Calibration** certificate included (ISO17025 (Ilac MRA))

Item No	Range	Depth	Resolu- tion	Accu- racy	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB
	mm	mm	mm	µm													
132010700	6-10	60	0.0001	±3	•	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update firmware
132018700	10-18	110		±3	•	•	•	•	•	•	•	•	•	•			
132050700	18-50	130		±3	•	•	•	•	•	•	•	•	•	•			
132050711		500		±3	•	•	•	•	•	•	•	•	•	•			
132050722		1000		±3	•	•	•	•	•	•	•	•	•	•			
132050744		2000		±3	•	•	•	•	•	•	•	•	•	•			
132160700	50-160	150		±3	•	•	•	•	•	•	•	•	•	•			
132160711		500		±3	•	•	•	•	•	•	•	•	•	•			
132160722		1000		±3	•	•	•	•	•	•	•	•	•	•			
132160744		2000		±3	•	•	•	•	•	•	•	•	•	•			
132250700	160-250	260		±5	•	•	•	•	•	•	•	•	•	•			
132250722		1000		±5	•	•	•	•	•	•	•	•	•	•			
132250744		2000		±5	•	•	•	•	•	•	•	•	•	•			
132450700		250-450		260	±8	•	•	•	•	•	•	•	•	•			
132450722	1000			±8	•	•	•	•	•	•	•	•	•	•			
132450744	2000			±8	•	•	•	•	•	•	•	•	•	•			
132900700	400-1000			440	±12	•	•	•	•	•	•	•	•	•			
132900722		1000		±12	•	•	•	•	•	•	•	•	•	•			
132900744		2000		±12	•	•	•	•	•	•	•	•	•	•			
132951700		250-1500		440	±8	•	•	•	•	•	•	•	•	•			
BORE GAUGES SETS																	
132160705	18-160		0.0001	±3	•	•	•	•	•	•	•	•	•	•	•	•	•
132450705	18-450		0.0001	±8	•	•	•	•	•	•	•	•	•	•	•	•	•
132990705	6-1000		0.0001	±12	•	•	•	•	•	•	•	•	•	•	•	•	•



DELIVERY SET

FREE VERSIONS OF MDS APP

USB DATA/CHARGING CABLE

CALIBRATION PROTOCOL

OPTIONAL

DATA MET BUTTON

DATA MET FOOTSWITCH

MDS DISPLAY UNIT

MDS SOFTWARE

STANDARD MDS app

UNIVERSAL CALIBRATION STANDS

