


TABLET MULTIFUNCTIONAL **MICS**
1.54" TOUCHSCREEN DISPLAY



DATAmet FUNCTIONS



COLOR GO / NOGO




COLOR MAX / MIN / RANGE




TIMER



FORMULA Ax^2+Bx+C




MEMORY 1000 values



MEMORY STATISTICS




TEMPERATURE COMPENSATION




DEVICE INFO, UPDATE



DISPLAY & ENERGY



RESOLUTION, mm/inch



WIRELESS to MDS app



WIRELESS & USB HID


- Industry 4.0 adopted depth caliper with computerized MICS system
- STANDARD type depth caliper or with PIN TIP or DOUBLE HOOK
- Functions: Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution select, Connection indication
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (ILac MRA))

DataMet DEPTH CALIPER

Item No	Range		Reso- lution	Accu- racy	Base	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB
	mm	inch	mm	μm	mm												
1432010157	0-150	0-6"	0,005	±15	102	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update
1432010207	0-200	0-8"		±20		•	•	•	•	•	•	•	•	•			
1432010307	0-300	0-12"		±25		•	•	•	•	•	•	•	•	•			
1432010507	0-500	0-20"		±40		•	•	•	•	•	•	•	•	•			
1432011007	0-1000	0-40"	0,01	±50	150	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update
1432012007	0-2000	0-80"		±70		•	•	•	•	•	•	•	•	•			
1432013007	0-3000	0-1200"		±90		•	•	•	•	•	•	•	•	•			

DataMet DEPTH CALIPER DOUBLE HOOK

Item No	Range		Reso- lution	Accu- racy	Base	Protection	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB
	mm	inch	mm	μm	mm													
1432020157	0-150	0-6"	0,005	±15	102	IP54	•	•	•	•	•	•	•	•	•	•	•	•
1432020307	0-300	0-12"		±25			•	•	•	•	•	•	•	•	•	•	•	•



DataMet DEPTH CALIPER PIN TIP

Item No	Range		Reso- lution	Accu- racy	Base	Pin	Protection	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB
	mm	inch	mm	μm	mm	mm													
1432030157	0-150	0-6"	0,005	±15	102	D 1,5	IP54	•	•	•	•	•	•	•	•	•	•	•	•
1432030307	0-300	0-12"		±25				•	•	•	•	•	•	•	•	•	•	•	•
1432030507	0-500	0-20"		±30				•	•	•	•	•	•	•	•	•	•	•	•

DataMet
interfaceCONNECTION
possibilitiesDOWNLOAD
MDS app WINDOWSDOWNLOAD
MDS app iOS, MacOSDOWNLOAD
MDS app ANDROID

DELIVERY SET



OPTIONAL

