



DATAmet MULTIFUNCTIONAL
ROUND 1.8" TOUCHSCREEN DISPLAY



Form D BALL Ø 1 , Ø 2

ADJUSTABLE SCALES



ANALOG



COMPARATOR



DIGITAL



DIGITAL BLACK

DATAmet FUNCTIONS

<p>ANALOG SCALE</p>	<p>COLOR GO / NOGO</p>	<p>COLOR MAX / MIN / RANGE</p>	<p>TIMER</p>	<p>TOUCH PROBE SETTINGS</p>	<p>FORMULA Ax^2+Bx+C</p>
<p>GRAPHIC MODE 1D/2D</p>	<p>MEMORY 2000 values</p>	<p>FOLDERS mode</p>	<p>MEMORY STATISTICS</p>	<p>TEMPERATURE COMPENSATION</p>	<p>PASSWORD</p>
<p>DISPLAY & ENERGY</p>	<p>RESOLUTION, mm/inch</p>	<p>WIRELESS to MDS app</p>	<p>WIRELESS & USB HID</p>	<p>HUB mode (2D, Probe)</p>	<p>DEVICE INFO, UPDATE</p>

- Industry 4.0 adopted **DataMet** Internal caliper gauge with computerized MICS system with hi-res Round 1,8" color Touchscreen
- **Contacts:** BALL (Ø2)
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- **Memory manager:** 50000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Modification **MODBUS RTU** data output (RS-485, 4-wire, 5-24V, GND, A, B) for industrial connections
- **MODBUS ASCII, MODBUS TCP/IP** for request
- **Calibration certificate** included (ISO17025 (Ilac MRA))

INTERNAL DataMet CALIPER GAUGE

Item No	Range	Span	Depth	Groove depth	Measur contact	Contact points	Resolution	Repeatability	Accuracy	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB
	mm	mm	mm	mm	mm	mm	mm	mm	µm													
134101547	5-15	10	35	0,8	2,3	Ball Ø 2	0,001	0,005	±10	•	•	•	•	•	•	•	•	•	•	•	Folders / 2000 val Long range / HID USB HID / Update	
134103047	10-30	20	85	1,2	5,2			0,005	±20	•	•	•	•	•	•	•	•	•	•	•		
134105047	30-50	20	85	2	7,2			0,005	±25	•	•	•	•	•	•	•	•	•	•	•		
134110047	50-100	50	235	2	11,7			0,02	±40	•	•	•	•	•	•	•	•	•	•	•		
134115047	100-150	50	235	2	11,7			0,02	±50	•	•	•	•	•	•	•	•	•	•	•		
134120047	150-200	50	235	2	11,7			0,02	±50	•	•	•	•	•	•	•	•	•	•	•		

MODBUS INTERNAL DataMet CALIPER GAUGE

Item No	Range	Span	Depth	Groove depth	Measur contact	Contact points	Resolution	Repeatability	Accuracy	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB	MODBUS RTU	MODBUS ASCII	MODBUS TCP/IP
	mm	mm	mm	mm	mm	mm	mm	mm	µm																
134101547M	5-15	10	35	0,8	2,3	Ball Ø 2	0,001	0,005	±10	•	•	•	•	•	•	•	•	•	•	•	Folders / 2000 val Long range / HID USB HID / Update	•			
134103047M	10-30	20	85	1,2	5,2			0,005	±20	•	•	•	•	•	•	•	•	•	•	•			•		
134105047M	30-50	20	85	2	7,2			0,005	±25	•	•	•	•	•	•	•	•	•	•	•			•	option	option
134110047M	50-100	50	235	2	11,7			0,02	±40	•	•	•	•	•	•	•	•	•	•	•			•		
134115047M	100-150	50	235	2	11,7			0,02	±50	•	•	•	•	•	•	•	•	•	•	•			•		
134120047M	150-200	50	235	2	11,7			0,02	±50	•	•	•	•	•	•	•	•	•	•	•			•		

DELIVERY SET

FREE VERSIONS OF MDS APP



USB DATA/CHARGING CABLE





CALIBRATION PROTOCOL



DataMet interface



CONNECTION possibilities



DOWNLOAD MDS app WINDOWS



OPTIONAL

DATA MET BUTTON



DATA MET FOOTSWITCH



MDS DISPLAY UNIT



MDS SOFTWARE



STANDARD MDS app



MODBUS protocol



DOWNLOAD MDS app iOS, MacOS





DOWNLOAD MDS app ANDROID

