



TAPE DRUM

CUSTOM RANGE FOR REQUEST

FORCE GAUGE FOR TENSILE LOAD 50N



DATA MET FUNCTIONS

<p>ANALOG SCALE</p>	<p>COLOR GO / NOGO</p>	<p>COLOR MAX / MIN / RANGE</p>	<p>TIMER</p>	<p>TOUCH PROBE SETTINGS</p>	<p>FORMULA Ax^2+Bx+C</p>
<p>GRAPHIC MODE 1D/2D</p>	<p>MEMORY 2000 values</p>	<p>FOLDERS mode</p>	<p>MEMORY STATISTICS</p>	<p>TEMPERATURE COMPENSATION</p>	<p>PASSWORD</p>
<p>DISPLAY & ENERGY</p>	<p>RESOLUTION, mm/inch</p>	<p>WIRELESS to MDS app</p>	<p>WIRELESS & USB HID</p>	<p>HUB mode (2D, Probe)</p>	<p>DEVICE INFO, UPDATE</p>

- Manual calibration stands for ruler & tape calibration
- High resolution 7" LED microscope
- Patents UA147069, UA151330
- Functions: On-line Graphic, Analog scale, Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction
- Measuring HUB: Wireless MICROTECH instrument connection, 2D mode,
- Memory manager: 2000 values, Folders system, Statistics mode,
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))

RULER DataMet CALIBRATOR

Item No	Range		Reso- lution	Accuracy	Micro- scope	Ruler magnetic fixator	Roll sliding system	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB
	mm	inch																	
258010003	0-1000	0-40"	0,01	±0,010+L/65	LED 7 inch	•	•	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update
258020003	0-2000	0-80"		±0,015+L/50		•	•	•	•	•	•	•	•	•	•	•			
258030003	0-3000	0-120"		±0,020+L/40		•	•	•	•	•	•	•	•	•	•	•			

RULER&TAPE DataMet CALIBRATOR

Item No	Range		Reso- lution	Accuracy	Micro- scope	Ruler magnetic fixator	Tape drum	Force gauge	Roll sliding system	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB
	mm	inch																			
258010005	0-1000	0-40"	0,01	±0,010+L/65	LED 7 inch	•	max 50m tape	Digital 50N	•	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update
258020005	0-2000	0-80"		±0,015+L/50		•			•	•	•	•	•	•	•	•	•	•			
258030005	0-3000	0-120"		±0,020+L/40		•			•	•	•	•	•	•	•	•	•	•			



DELIVERY SET

FREE VERSIONS OF MDS APP

USB DATA/CHARGING CABLE

ILAC-MRA CALIBRATION PROTOCOL

OPTIONAL

DATA MET BUTTON

DATA MET FOOTSWITCH

MDS DISPLAY UNIT

MDS SOFTWARE