



CUSTOM RANGE AND CONFIGURATION FOR REQUEST

COMPUTERIZED MICS SYSTEM MAIN FUNCTIONS

| | | | | | |
|------------------------------------|-----------------------------------|---------------------------------------|--------------------------------------|--|--|
| <p>ANALOG SCALE</p> | <p>COLOR GO / NOGO</p> | <p>COLOR MAX / MIN / RANGE</p> | <p>TIMER</p> | <p>TOUCH PROBE SETTINGS</p> | <p>FORMULA Ax^2+Bx+C</p> |
| <p>GRAPHIC MODE 1D/2D</p> | <p>MEMORY 2000 values</p> | <p>FOLDERS mode</p> | <p>MEMORY STATISTICS</p> | <p>TEMPERATURE COMPENSATION</p> | <p>PASSWORD</p> |
| <p>DISPLAY & ENERGY</p> | <p>RESOLUTION, mm/inch</p> | <p>WIRELESS to MDS app</p> | <p>WIRELESS & USB HID</p> | <p>HUB mode (2D, Probe)</p> | <p>DEVICE INFO, UPDATE</p> |

LINEAR SCALE COMPUTERIZED WITH MAGNIFIER

- Industry 4.0 adopted linear scale with computerized MICS system (Patents US10184772, UA174949, UA126928)
- MICRON with **SWISS made reading system** resolution **1micron** (0,0005/0,001/0,01/0,1mm selection)
- Magnifier 10x loupe with scale or **MICROSCOPE** with 7" display and 12Mp camera
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution select, Connection indication
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))

LINEAR SCALE COMPUTERIZED WITH MAGNIFIER

| Item No | Range | | Reso- lution | Accu- racy | Vision | Protection | 2D connection | Graphic | Analog scale | Preset | Go/NoGo | Max/Min | Formula | Timer | Temp comp | Linear corr | Calibr date | Recharge | Memory | Folders | WIRELESS | USB HID | MODBUS | | | | | |
|-----------|--------|-------|-----------------|---------------|---------------|------------|---------------|---------|--------------|--------|---------|---------|---------|-------|-----------|-------------|-------------|----------|----------|---------|----------|---------|--------|---|---|---|---|---|
| | mm | inch | mm | µm | | | | | | | | | | | | | | | | | | | | | | | | |
| 142503157 | 0-300 | 0-12" | 0,0005 | ±12 | 10x magnifier | IP54 | • | • | • | • | • | • | • | • | • | • | • | • | 2000 val | • | • | • | OPTION | | | | | |
| 142505157 | 0-500 | 0-20" | | ±15 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | | | |
| 142506157 | 0-600 | 0-24" | | ±20 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | | | |
| 142508157 | 0-800 | 0-32" | | ±20 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | • | | |
| 142510157 | 0-1000 | 0-40" | | ±25 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | • | • | |
| 142515157 | 0-1500 | 0-60" | | ±30 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | • | • | • |
| 142520157 | 0-2000 | 0-80" | | ±40 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | • | • | • |

LINEAR SCALE COMPUTERIZED WITH LED MICROSCOPE

| Item No | Range | | Reso- lution | Accu- racy | Vision | Protection | 2D connection | Graphic | Analog scale | Preset | Go/NoGo | Max/Min | Formula | Timer | Temp comp | Linear corr | Calibr date | Recharge | Memory | Folders | WIRELESS | USB HID | MODBUS | | | | | | |
|-----------|--------|-------|-----------------|---------------|---------------|------------|---------------|---------|--------------|--------|---------|---------|---------|-------|-----------|-------------|-------------|----------|----------|---------|----------|---------|--------|---|---|---|---|---|---|
| | mm | inch | mm | µm | | | | | | | | | | | | | | | | | | | | | | | | | |
| 142503177 | 0-300 | 0-12" | 0,0005 | ±12 | 10x magnifier | IP54 | • | • | • | • | • | • | • | • | • | • | • | • | 2000 val | • | • | • | OPTION | | | | | | |
| 142505177 | 0-500 | 0-20" | | ±15 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | • | • | • | |
| 142506177 | 0-600 | 0-24" | | ±20 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | • | • | • | • |
| 142508177 | 0-800 | 0-32" | | ±20 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | • | • | • | • |
| 142510177 | 0-1000 | 0-40" | | ±25 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | • | • | • | • |
| 142515177 | 0-1500 | 0-60" | | ±30 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | • | • | • | • |
| 142520177 | 0-2000 | 0-80" | | ±40 | | | • | • | • | • | • | • | • | • | • | • | • | • | | • | • | • | | • | • | • | • | • | • |

DOWNLOAD APP



COMPLECTATION



OPTIONAL

