


- Industry 4.0 adopted **DataMet** test indicator with computerized MICS system color Touchscreen
- MODIFICATION MODBUS RTU data output (RS-485, 4-wire, 5-24V, GND, A, B) for industrial connections
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- MODIFICATION MODBUS RTU data output (RS-485, 4-wire, 5-24V, GND, A, B) for industrial connections
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- **Calibration** certificate included (ISO17025 (Ilac MRA))



MODIFICATION MODBUS RTU

0,1µm

Item No	Range		Resol.	Accu- racy	Probe	Measur- ing Force	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB	MODBUS RTU	
	mm	inch	mm	µm	mm	N															
120129018	-0.8	-0.03"	0,0001	±5	12,8	0,1-0,18	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
120129018M	+0.8	+0.03"					•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

DataMet interface

CONNECTION possibilities

MODBUS protocol

VIDEO

DELIVERY SET

FREE VERSIONS OF MDS APP

USB DATA/CHARGING CABLE

OPTIONAL

DATA MET BUTTON

DATA MET FOOTSWITCH

MDS DISPLAY UNIT

MDS SOFTWARE

STANDS

DOWNLOAD MDS app WINDOWS

DOWNLOAD MDS app iOS, MacOS

DOWNLOAD MDS app ANDROID