



CARBON FIBER TUBE

SOLID CARBON TUBES

DATA MET FUNCTIONS

<p>ANALOG SCALE</p>	<p>COLOR GO / NOGO</p>	<p>COLOR MAX / MIN / RANGE</p>	<p>TIMER</p>	<p>TOUCH PROBE SETTINGS</p>	<p>FORMULA Ax^2+Bx+C</p>
<p>GRAPHIC MODE 1D/2D</p>	<p>MEMORY 2000 values</p>	<p>FOLDERS mode</p>	<p>MEMORY STATISTICS</p>	<p>TEMPERATURE COMPENSATION</p>	<p>PASSWORD</p>
<p>DISPLAY & ENERGY</p>	<p>RESOLUTION, mm/inch</p>	<p>WIRELESS to MDS app</p>	<p>WIRELESS & USB HID</p>	<p>HUB mode (2D, Probe)</p>	<p>DEVICE INFO, UPDATE</p>

- CARBON Tubular **DataMet** Inside micrometers with range up to 10m
- Light and solid carbon extension rods
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution select, Connection indication
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))

Item No	Range		Reso- lution	Accu- racy	Tube D	Extension rods	Proof	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB	
	mm	inch																		mm
133800101	150-1000	6-40"	0,0001	±15	22	25, 50 (2pcs), 100 (1pcs), 200 (1pcs), 400 (1pcs)	IP65	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update	
133800151	150-1500	6-60"		±15		25, 50 (2pcs), 100 (2pcs), 200 (1pcs), 400 (2pcs)		•	•	•	•	•	•	•	•	•				•
133800201	150-2100	6-85"		±20	25, 50 (1pcs), 100 (1pcs), 200 (1pcs), 400 (4pcs)	•		•	•	•	•	•	•	•	•	•				
133800301	150-3000	6-120"		±30	32	25, 50 (2pcs), 100 (1pcs), 200 (2pcs), 400 (3pcs), 1000 (1pcs)		•	•	•	•	•	•	•	•	•				•
133800401	150-4000	6-160"		±40		25, 50 (2pcs), 100 (1pcs), 200 (2pcs), 400 (3pcs), 1000 (2pcs)		•	•	•	•	•	•	•	•	•				•
133800501	150-5000	6-200"		±50	50	25, 50 (2pcs), 100 (1pcs), 200 (2pcs), 400 (3pcs), 1000 (3pcs)		•	•	•	•	•	•	•	•	•				•
133800601	150-6000	6-240"		±60		25, 50 (2pcs), 100 (1pcs), 200 (2pcs), 400 (3pcs), 1000 (4pcs)		•	•	•	•	•	•	•	•	•				•
133800801	150-8000	6-320"		±80		25, 50 (2pcs), 100 (1pcs), 200 (2pcs), 400 (3pcs), 1000 (6pcs)		•	•	•	•	•	•	•	•	•				•
133801001	150-10000	6-400"		±100		25, 50 (2pcs), 100 (1pcs), 200 (2pcs), 400 (3pcs), 1000 (8pcs)		•	•	•	•	•	•	•	•	•				•



DELIVERY SET

FREE VERSIONS OF MDS APP

USB DATA/CHARGING CABLE

CALIBRATION PROTOCOL

DataMet interface

CONNECTION possibilities

DOWNLOAD MDS app WINDOWS

DOWNLOAD MDS app iOS, MacOS

DOWNLOAD MDS app ANDROID

OPTIONAL

DATA MET BUTTON

DATA MET FOOTSWITCH

MDS DISPLAY UNIT

MDS SOFTWARE

STANDARD MDS app

UNIVERSAL CALIBRATION STANDS