


- Industry 4.0 adopted DataMet Braille dot thickness gauge
- Granite base gr.00
- Functions: Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- Quick reading system (50 value/sec)
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- MODIFICATION MODBUS RTU data output (RS-485, 4-wire, 5-24V, GND, A, B) for industrial connections
- Calibration certificate included (ISO17025 (Ilac MRA))



| Item No    | Range | Resolution | Accuracy | Depth | Contact points D | Base          | Preset | Go/NoGo | Max/Min | Formula | Timer | FW update | Recharge | Memory | WIRELESS | USB | MODBUS RTU |
|------------|-------|------------|----------|-------|------------------|---------------|--------|---------|---------|---------|-------|-----------|----------|--------|----------|-----|------------|
| 137022079  | mm    | mm         | μm       | mm    | mm               |               |        |         |         |         |       |           |          |        |          |     |            |
| 137022079M | 0-10  | 0.0001     | ±3       | 60    | 7.8              | granite gr.00 | •      | •       | •       | •       | •     | •         | •        | •      | •        | •   | •          |



DOWNLOAD  
MDS app WINDOWS




DOWNLOAD  
MDS app iOS, MacOS



DOWNLOAD  
MDS app ANDROID

## DELIVERY SET



## OPTIONAL

