

- Industry 4.0 adopted **DataMet** Disk Snap gauge
- Disk Anvils with D=20, 35 or 50mm
- Supplying with computerized **DataMet** indicator with 0,1 micron resolution
- **Functions:** Go/NoGo, Max/Min, MultiPreset, Formula, Timer, Linear correction, Temperature correction
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **Quick reading system** (50 value/sec)
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- **Calibration** certificate included (ISO17025 (Ilac MRA))



Item No	Range		Reso- lution	Accu- racy	Depth	Anvils type	Travel	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB				
	mm	inch																		mm	µm	mm	mm
115050527	0-50	0-2"	0,0001	±4	32	D 20mm	3	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID				
115050537				±5		D 35mm		•	•	•	•	•	•	•	•	•							
115050557				±7		D 50mm		•	•	•	•	•	•	•	•	•							
115051027	50-100	2-4"		±4	62	D 20mm		•	•	•	•	•	•	•	•	•				•	•	•	•
115051037				±5		D 35mm		•	•	•	•	•	•	•	•	•							
115051057				±7		D 50mm		•	•	•	•	•	•	•	•	•				•			
115051527	100-150	4-6"		±6	85	D 20mm		•	•	•	•	•	•	•	•	•				•	•	•	•
115051537				±7		D 35mm		•	•	•	•	•	•	•	•	•							
115051557				±9		D 50mm		•	•	•	•	•	•	•	•	•				•			
115052027	150-200	6-8"		±7	110	D 20mm		•	•	•	•	•	•	•	•	•				•	•	•	•
115052037				±8		D 35mm		•	•	•	•	•	•	•	•	•							
115052057				±9		D 50mm		•	•	•	•	•	•	•	•	•				•			



## DELIVERY SET

FREE VERSIONS OF MDS APP

CALIBRATION PROTOCOL

USB DATA/CHARGING CABLE

## OPTIONAL

DATAmet BUTTON

DATAmet FOOTSWITCH

MDS DISPLAY UNIT

MDS SOFTWARE

STANDARD MDS app