

- Semi-automatic vision measuring machine
- Granite base and column and precision Hiwin linear guides
- Manual control X, Y axis and Motorized Z-axis
- Programmable led four zone ring surface light, led bottom parallel light, **coaxial light**
- Manual 6.5:1 zoom with electronic feedback to automatic identification in software
- **5Mp Hi-res AUTOFOCUS camera**
- Completion 24" Windows PC with innovative 2D measuring software with CAD import/comparison module and multilanguage interface
- Optional Renishaw touchprobe
- **Calibration** certificate included (ISO17025 (Ilac MRA))



MICROTECH
EvoMet

24" WINDOWS PC WITH SOFTWARE

MOTORIZED Z-AXIS
AUTOFOCUS
COAXIAL LIGHT
5 MP CAMERA

MULTILINGUE INTERFACE



ENGLISH
TEST, DATABASE,
CALIBRATE, OPTION




GERMAN
TEST, DATENBANK,
KALIBRIERUNG, OPTION



UKRAINIAN
ТЕСТ, БАЗА ДАНИХ,
КАЛІБРУВАННЯ, ОПЦІЯ

Item No	Type	Magnification	Field of view	Camera	Working distance	Accuracy	Resolution	Table travel	Load capacity	Lighting	Indication system
			mm		mm		mm	mm	kg		
281010325	MX-320	18-195x (6.5x manual zoom)	8.1-1.3	5 Mp autofocus	90	2.1+L/100	0,0005	300x200x200	25	-programmable led four zone ring surface light -led bottom parallel light - coaxial light	24" Windows PC with 2D Measuring software with CAD function

DELIVERY SET



OPTIONAL

