



SWISS
READING
SYSTEM

IP67



SWISS
ELECTRONICS



MODIFICATION WITH BUILT-IN MULTIMODE
WIRELESS DATA TRANSFER MODULE



SwissMet IP67 FUNCTIONS

PrE **Unit** **Hold**

PRESET

mm/inch

HOLD

SLEEP (SIS)

IP67



SWISS
ELECTRONICS

Auto ON/OFF

IP 67 (IEC60529)

Swiss electronics

MDS APP



WIRELESS MDS app

HID



WIRELESS HID



EXTERNAL CERAMIC TIPPED JAWS



- Waterproof **IP67** Swiss electronics with 0.001mm resolution
- High accuracy up to $\pm 20\mu\text{m}$ on external jaws (internal and depth according ISO13385)
- **MODIFICATION** with External ceramic tipped jaws non-magnetic, non-conductive and wear-resistant
- **MODIFICATION** with **3 MODES DATA TRANSFER**: WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC
- Calibration certificate included (ISO17025 (Ilac MRA))

MICRON SWISSMET IP67 DIGITAL CALIPER

Item No	Range		Reso- lution	Accu- racy	Jaws	Protection	Round rod	Preset	mm/inch	Auto on/off
	mm	inch	mm	μm						
141073122	0-150	0-6"	0,001	± 15	40/16	IP-67		•	•	•
141073122R							•	•	•	•
141073222	0-200	0-8"		± 15	50/17			•	•	•
141073322	0-300	0-12"		± 20	60/20		•	•	•	•



WIRELESS MICRON SWISSMET IP67 DIGITAL CALIPER

Item No	Range		Reso- lution	Accu- racy	Jaws	Protection	Round rod	Preset	mm/inch	Auto on/off	WIRELESS
	mm	inch	mm	μm							
141073192	0-150	0-6"	0,001	± 15	40/16	IP-67		•	•	•	•
141073192R							•	•	•	•	•
141073292	0-200	0-8"		± 15	50/17			•	•	•	•
141073392	0-300	0-12"		± 20	60/20		•	•	•	•	•



CERAMIC MICRON SWISSMET IP67 DIGITAL CALIPER

Item No	Range		Reso- lution	Accu- racy	Jaws	Protection	Preset	mm/inch	Auto on/off
	mm	inch	mm	μm					
141073122K	0-150	0-6"	0,001	± 15	40/16	IP-67	•	•	•
141073222K	0-200	0-8"		± 15	50/17		•	•	•
141073322K	0-300	0-12"		± 20	60/20		•	•	•



CERAMIC WIRELESS MICRON SWISSMET IP67 DIGITAL CALIPER

Item No	Range		Reso- lution	Accu- racy	Jaws	Protection	Preset	mm/inch	Auto on/off	WIRELESS
	mm	inch	mm	μm						
141073192K	0-150	0-6"	0,001	± 15	40/16	IP-67	•	•	•	•
141073292K	0-200	0-8"		± 15	50/17		•	•	•	•
141073392K	0-300	0-12"		± 20	60/20		•	•	•	•



DELIVERY SET



OPTIONAL

