

- **DataMet** Offset caliper
- Computerized **MICS** indication system with 0.005 resolution
- **E-Force** control module with Force selection 1-20N, color indication, AUTO-Force mode, Force indication
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution select, Connection indication
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- OPTIONAL **MODBUS RTU** data output (RS-485, 4-wire, 5-24V, GND, A, B) for industrial connections
- **Calibration certificate** included (ISO17025 (Ilac MRA))



Item No	Range	Jaws		Reso- lution	Accu- racy	Force	Protection	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB	
		slide	fix																		
141740157	0-150	110	40	0,005	±20	1-20	IP54	•	•	•	•	•	•	•	•	•	•	•	•	•	•
141740307	0-300	130	60	0,005	±30	1-20	IP54	•	•	•	•	•	•	•	•	•	•	•	•	•	•

DOWNLOAD
MDS app WINDOWS

DOWNLOAD
MDS app iOS, MacOS

DOWNLOAD
MDS app ANDROID



DELIVERY SET

FREE VERSIONS OF MDS APP

CALIBRATION PROTOCOL

USB DATA/CHARGING CABLE

OPTIONAL

DATA MET BUTTON

DATA MET FOOTSWITCH

MDS DISPLAY UNIT

MDS SOFTWARE

STANDARD MDS app