

DataMet MULTIFUNCTIONAL
ROUND 1.8" TOUCHSCREEN DISPLAY



Form A CONE R 0,3, R 0,5

ADJUSTABLE SCALES



ANALOG



COMPARATOR



DIGITAL



DIGITAL BLACK

DataMet FUNCTIONS

<p>ANALOG SCALE</p>	<p>COLOR GO / NOGO</p>	<p>COLOR MAX / MIN / RANGE</p>	<p>TIMER</p>	<p>TOUCH PROBE SETTINGS</p>	<p>FORMULA Ax^2+Bx+C</p>
<p>GRAPHIC MODE 1D/2D</p>	<p>MEMORY 2000 values</p>	<p>FOLDERS mode</p>	<p>MEMORY STATISTICS</p>	<p>TEMPERATURE COMPENSATION</p>	<p>PASSWORD</p>
<p>DISPLAY & ENERGY</p>	<p>RESOLUTION, mm/inch</p>	<p>WIRELESS to MDS app</p>	<p>WIRELESS & USB HID</p>	<p>HUB mode (2D, Probe)</p>	<p>DEVICE INFO, UPDATE</p>

- Industry 4.0 adopted **DataMet** Internal caliper gauge with computerized MICS system with hi-res Round 1,8" color Touchscreen
- **Contacts:** CONE (R0.3/R0.5)
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- **Memory manager:** 50000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Modification **MODBUS RTU** data output (RS-485, 4-wire, 5-24V, GND, A, B) for industrial connections
- **MODBUS ASCII, MODBUS TCP/IP** for request
- **Calibration** certificate included (ISO17025 (Ilac MRA))

INTERNAL DataMet CALIPER GAUGE

Item No	Range	Span	Depth	Groove depth	Measur contact	Contact points	Reso- lution	Repea- tability	Accu- racy	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB	
	mm	mm	mm	mm	mm	mm	mm	mm	µm														
134102507	5-25	20	35	1	1,5	Cone R 0,3	0,001	0,005	±15	•	•	•	•	•	•	•	•	•	•	•	Folders / Long range USB HID /		
134104007	20-40	20	80	3	6,5	Cone R 0,5		0,005	±15	•	•	•	•	•	•	•	•	•	•	•			
134106007	40-60	20	80	3	8,5			0,005	±15	•	•	•	•	•	•	•	•	•	•	•			

MODBUS INTERNAL DataMet CALIPER GAUGE

Item No	Range	Span	Depth	Groove depth	Measur contact	Contact points	Reso- lution	Repea- tability	Accu- racy	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB	MODBUS RTU	MODBUS ASCII	MODBUS TCP/IP	
	mm	mm	mm	mm	mm	mm	mm	mm	µm																	
134102507M	5-25	20	35	1	1,5	Cone R 0,3	0,001	0,005	±15	•	•	•	•	•	•	•	•	•	•	•	Folders / Long range USB HID /					
134104007M	20-40	20	80	3	6,5	Cone R 0,5		0,005	±15	•	•	•	•	•	•	•	•	•	•	•				option	option	
134106007M	40-60	20	80	3	8,5			0,005	±15	•	•	•	•	•	•	•	•	•	•	•		•				

DELIVERY SET

FREE VERSIONS OF MDS APP

USB DATA/CHARGING CABLE

CALIBRATION PROTOCOL

DataMet interface

CONNECTION possibilities

DOWNLOAD MDS app WINDOWS

DOWNLOAD MDS app iOS, MacOS

OPTIONAL

DATA MET BUTTON

DATA MET FOOTSWITCH

MDS DISPLAY UNIT

MDS SOFTWARE

STANDARD MDS app

MODBUS protocol

DOWNLOAD MDS app ANDROID